



Finish Tech

START WITH THE FINISH

90 Industrial Drive
Ivyland, PA 18974
Phone: 215-396-8800
Fax: 215-396-8810
Toll-free: 866-396-8898

PERFORMANCE OF SCRATCH RESISTANT FINISH (SRF)

Our SRF finish is available on all our polyester products. These products offer a truly superior combination of scratch, abrasion, heat, water, solvent, stain and chemical resistance.

Compare and see the difference!

Peelsheet: All products are available with peelsheet. Performance (i.e., adhesion/clean release) of each type of peelsheet is time and temperature dependent. Each application must be thoroughly evaluated.

FTC's unique SRF qualities and advantage:

- 60 degree gloss over 95%
- Passes Cross Hatch Adhesion
- Was found to be superior to EB and HPL when scratching with Rotary 0000 steel - wool
- Resistant to boiling water
- Solvent and Stain Resistant

We tested our product with each of the following agents. Each agent was allowed to be in contact with product overnight and was then wiped off with a mild detergent or glass cleaner.

Water	NE*	Milk	NE*
Ethyl Alcohol	NE*	10% Citric Acid	NE*
Isopropyl Alcohol	NE*	Mustard	NE*
Naptha	NE*	Vinegar	NE*
Lipstick	NE*	Methyl Ethyl Ketone	NE*
Ink-Blue	NE*	Grape Juice	NE*
5% Soap Solution	NE*	Rit Dye	NE*
5% Detergent Solution	NE*	Mercurochrome	NE*
Household Ammonia	NE*	Merthiolate	NE*
Ketchup	NE*	Wax Crayon	NE*
Vegetable Cooking Oil	NE*	Shoe Polish	NE*
1% Trisodium Phospate	NE*	Ball Point Pen ink	NE*
Coffee	NE*	Felt Pen	NE*
Tea	NE*	Stamp Pad Ink	NE*

***NO EFFECT**

These lab results are provided as a key service. All products are sold upon condition that purchaser shall make their own tests and judgements. NO WARRANTY or merchantability or fitness for any purpose is implied neither does this constitute sellers product specifications.